

CLAIMS

What is claimed is:

1. A cupholding plate comprising:

a plate support surface having a peripheral edge;

5 a stiffened, circular outer flange rim circumscribing the entire plate support surface at an elevation above the plate support surfaces;

an upwardly curving peripheral rim connecting between said plate support surface and said outer flange;

10 a pair of partition elements connect at a centerpoint of said plate support surface and radiating out to said outer flange, each partition element having a flat upper apex connecting to said circular outer flange at the flanges elevation, and transitions smoothly to the elevation of the plate support surface by a curving partition sidewall having a similar curvature with the upwardly curving peripheral rim;

15 said partition elements forming an acute angle at said centerpoint at a base of said partition sidewall such that a first large compartment is formed at the acute angle between the partition elements and the outer flange;

20 a cup retaining orifice formed within said plate support surface and positioned such as to intersect at the outer circumference of the plate the cup support rim;

a stiffened cup support rim circumscribing said cup retaining orifice;

a third partition element connecting said cup support rim with said  
flat upper apex of said other partition elements, said third partition element  
having a flat upper apex that transitions smoothly to the elevation of the plate  
support surface by a curving partition sidewall having a similar curvature with the  
upwardly curving peripheral rim; and

a stiffened cup support rim contained within the outer circumference of the  
plate is a cup retaining orifice and wherein said cup support rim intersects with  
said peripheral rim at said plate peripheral edge, such that both said peripheral  
rim and said cup support rim are superimposed about each other along a small  
arc along their respective circumferences.

2. The cupholding plate of Claim 1, wherein said single structural element is  
formed of a material selected from the group comprising foam, paper, pressed  
paper, and plastic.

3. A cupholding plate comprising:

a plate support surface having a peripheral edge;

a stiffened, circular outer flange rim circumscribing the entire plate  
support surface at an elevation above the plate support surfaces;

an upwardly curving peripheral rim connecting between said plate support surface and said outer flange;

5 a single partition elements bisecting said plate support surface through a centerpoint of said plate support surface between said outer flange, said partition element having a flat upper apex connecting to said circular outer flange at the flanges elevation, and transitions smoothly to the elevation of the plate support surface by a curving partition sidewall having a similar curvature with the upwardly curving peripheral rim;

10 a cup retaining orifice formed within said plate support surface and positioned such as to intersect at the outer circumference of the plate the cup support rim;

a stiffened cup support rim circumscribing said cup retaining orifice;

15 a stiffened cup support rim contained within the outer circumference of the plate is a cup retaining orifice and wherein said cup support rim intersects with said peripheral rim at said plate peripheral edge, such that both said peripheral rim and said cup support rim are superimposed about each other along a small arc along their respective circumferences.

4. The cupholding plate of Claim 3, wherein said single structural element is  
20 formed of a material selected from the group comprising foam, paper, pressed

paper, and plastic.

5. A cupholding plate comprising:

a plate support surface having a peripheral edge;

a stiffened, circular outer flange rim circumscribing the entire plate  
support surface at an elevation above the plate support surfaces;

an upwardly curving peripheral rim connecting between said plate  
support surface and said outer flange;

a cup retaining orifice formed within said plate support surface and  
positioned such as to intersect at the outer circumference of the plate the cup  
support rim;

a stiffened cup support rim circumscribing said cup retaining orifice;

a stiffened cup support rim contained within the outer  
circumference of the plate is a cup retaining orifice and wherein said cup support  
rim intersects with said peripheral rim at said plate peripheral edge, such that  
both said peripheral rim and said cup support rim are superimposed about each  
other along a small arc along their respective circumferences.

6. The cupholding plate of Claim 5, wherein said single structural element is  
formed of a material selected from the group comprising foam, paper, pressed  
paper, and plastic.